

2208, 2301S0S8

EN


Ribbed driver pulley puller

SLO


Snemalec narebrenih jermenic

 **UNIOR**<sup>®</sup>  
[www.uniortools.com](http://www.uniortools.com)


## RIBBED PULLEY DIMENSIONS




**SHORT BEAM, min. A = Ø40mm, max. A = Ø160mm**  
**LONG BEAM, min. A = Ø90mm, max. A = Ø240mm**  
KRATKA glava, min. A = Ø40mm, max. A = Ø160mm  
DOLGA glava, min. A = Ø90mm, max. A = Ø240mm



**SHORT BEAM, min. C = Ø75mm, max. C = Ø150mm**  
**LONG BEAM, min. C = Ø125mm, max. C = Ø240mm**  
KRATKA glava, min. C = Ø75mm, max. C = Ø150mm  
DOLGA glava, min. C = Ø125mm, max. C = Ø240mm




**SHORT BEAM, min. B = Ø38mm, max. B = Ø130mm**  
**LONG BEAM, min. B = Ø90mm, max. B = Ø205mm**  
KRATKA glava, min. B = Ø38mm, max. B = Ø130mm  
DOLGA glava, min. B = Ø90mm, max. B = Ø205mm




**SHORT BEAM, min. D = Ø75mm, max. D = Ø150mm**  
**LONG BEAM, min. D = Ø125mm, max. D = Ø240mm**  
KRATKA glava, min. D = Ø75mm, max. D = Ø150mm  
DOLGA glava, min. D = Ø125mm, max. D = Ø240mm


## USAGE




**Disassembly of driver pulley with ribbed jaws.** / Demontaža jermenice z snemalno šapo z ozobjem.



**Disassembly of double height driver pulley with ribbed jaws and additional extensions.** / Demontaža dvojne debeline jermenice z snemalno šapo z ozobjem ter nastavkom.



**Disassembly of driver pulley with hook jaw.** / Demontaža jermenice z snemalnim kavljem.



**Disassembly of driver pulley with two M10 screws.** / Demontaža jermenice s pomočjo dveh vijakov M10.



**Unior d.d.**  
Kovaška cesta 10  
3214 Zreče, Slovenia  
T: +386 3 757 81 00  
F: +386 3 576 26 43  
unior@unior.si  
www.uniortools.com